

Data Sheet

METAL CONSUMER UNITS



- Metal Clad Consumer Unit
- Complete with Main Switch
- Integrated Spirit Level
- Designed to BS EN 61439
- Accepts MCB's or RCBO's
- Compatible with Surge Protection Devices range of SPD's

Size	Part Number	Main Switch Rating	Dimensions (cm)
2 Way	CUL2M	63 Amp	L 14 x H 24.5 x D 8.5
6 Way	CUL6M	100 Amp	L 21 x H 24.5 x D 8.5
8 Way	CUL8M	100 Amp	L 25 x H 24.5 x D 8.5
12 Way	CUL12M	100 Amp	L 32 x H 24.5 x D 8.5
14 Way	CUL14M	100 Amp	L 35.5 x H 24.5 x D 8.5
16 Way	CUL16M	100 Amp	L 39.5 x H 24.5 x D 8.5
20 Way	CUL20M	100 Amp	L 46.5 x H 24.5 x D 8.5

TECHNICAL SPECIFICATIONS

Standard	BS EN 61439-3
Rated Voltage	230V AC
Rated Insulated Voltage	500V AC
Rated Impulse Withstand Voltage	4kV
Rated Frequency	50/60Hz
Rated Current of the Assembly	100A
IP Rating	IP30
Mechanical Impact Protection	IK05

Data Sheet

MAIN SWITCH



- 2 Pole Main Switch
- 63 Amp and 100 Amp Available
- Designed to BS EN 60947-3

TECHNICAL SPECIFICATIONS

Standard	BS EN 60947-3
Number of Poles	2 Pole
Rated Current	63A or 100A
Rated Voltage	400V AC
Rated Insulated Voltage	415V
Rated Impulse Withstand Voltage	4kV
Rated Frequency	50/60Hz
IP Rating	IP30
Width	36mm